



Kvaser Leaf Light HS V2 OBDII

PWR
CAN

KVASER LEAF LIGHT HS V2 OBDII

EAN 73-30130-00732-1

The Leaf Light v2 OBDII provides a simple way of connecting a PC with a vehicle's on-board computer by means of USB 2.0 connector and a 16-pin OBDII-compliant CAN connector. Having made its name as the workhorse of USB to CAN interfaces, Kvaser's Leaf Light product series provides reliable, low cost tools for connecting any CAN network to a PC or mobile computer in vehicle diagnostic applications and beyond.

KVASER LEAF LIGHT HS V2 OBDII

EAN 73-30130-00732-1

Major Features

- The Kvaser Leaf Light HS V2 OBDII offers loss free transmission and reception of standard and extended CAN messages on the CAN bus.
- Supports high-speed USB and has an OBD2-compliant connector.
- 8000 messages per second, each time-stamped with 100 microsecond accuracy.
- Supports both 11-bit (CAN 2.0A) and 29-bit (CAN 2.0B active) identifiers.
- High-speed CAN connection (compliant with ISO 11898-2), up to 1 Mbit/s.
- Galvanic isolation, enhancing protection from power surges or electrical shocks.

Technical Data

Bitrate	40-1000 kbps
Temp Range	-20 - 75 °C
Timestamp	100
Messages Per Second Receive	8000 mps
Messages Per Second Sending	8000 mps
Weight	100 g
Length	100 mm
Height	20 mm
Channels	1
Certificates	CE, RoHS
Interfaces	USB
Categories	PC Interfaces, Interfaces
OS	Windows 10, 8, 7, XP, Vista and Linux
Connectors	OBD-II /J1962
Buffers	On Board Buffer
Galvanic Isolation	Yes
Error Frame Generation	No
Error Counters Reading	No
Silent Mode	No
Material	PA66
Sound	No
Current Consumption	Typical 90mA



WARRANTY

2-Year Warranty. See our General Conditions and Policies for details.

SUPPORT

Free Technical Support on all products available by contacting support@kvaser.com

SOFTWARE

Documentation, software and drivers can be downloaded for free at: www.kvaser.com/downloads

Kvaser CANlib SDK is a free resource that includes everything you need to develop software for the Kvaser CAN interfaces. Includes full documentation and many program samples, written in C, C++, C#, Delphi, Java, Python and Visual Basic.

All Kvaser CAN interface boards share a common software API. Programs written for one interface type will run without modifications on the other interface types!

J2534 Application Programming Interface available.

RP1210A Application Programming Interface available.

Online documentation in Windows HTML-Help and Adobe Acrobat format.