



Kvaser Q-cable

EAN: 73-30130-00199-2

The Q-Cable is a 0.3m (approx. 0.98 ft) long adapter cable for the Kvaser PCICanx 4xHS and Kvaser PCICan 4xHS boards. A DSUB male connector connects to the PCICan board, whilst four DSUB male connectors connect to the CANbus.

### Major Features

- Adapter cable designed for the Kvaser PCICanx 4xHS and the Kvaser PCICan 4xHS boards.
- One molded 25 pin DSUB male connector with thumbscrews that connects to the CAN interface board
- Four molded 9 pin DSUB male connectors with thumbscrews for the CAN bus
- The Q cable is also available in a 3m length Low Smoke Zero Halogen version (Item no. 00340-8) to protect people and equipment from toxic and corrosive gases



Kvaser Q-cable

## **Warranty**

- 2-Year Warranty. See our General Conditions and Policies for details.

## **Support**

- Free Technical Support on all products available by contacting [support@kvaser.com](mailto:support@kvaser.com).



## TECHNICAL DATA - KVASER Q-CABLE

|                                 |                              |
|---------------------------------|------------------------------|
| SOUND                           | No                           |
| STATUS                          | Active                       |
| OPERATING TEMPERATURE RANGE (C) | -30.00 to 85.00              |
| ERROR COUNTERS READING          | N/A                          |
| NETWORK CHANNEL(S)              |                              |
| CASING MATERIAL                 | Durable thermoplastic rubber |
| CONNECTOR                       | N/A                          |
| ERROR COUNTERS READING          | No                           |
| GALVANIC ISOLATION              | N/A                          |
| CAN FD                          | No                           |
| # OF CAN CHANNELS               | 4                            |
| MAXIMUM BITRATE (KBPS)          | N/A                          |
| OPERATING TEMPERATURE RANGE (C) | -30.00 to 85.00              |
| LENGTH (MM)                     | 300                          |
| MINIMUM BITRATE (KBPS)          | N/A                          |
| ERROR FRAME GENERATION          | No                           |
| SILENT MODE                     | N/A                          |
| ON-BOARD RX BUFFER              | N/A                          |
| ERROR FRAME GENERATION          | N/A                          |
| MAXIMUM BITRATE (KBPS)          | N/A                          |
| PC INTERFACE                    | Cable                        |
| WEIGHT (G)                      | 200.0                        |
| ON-BOARD RX BUFFER              | No                           |
| PC INTERFACE                    | Cable                        |
| API, LICENCED                   | None                         |
| API, FREE                       | N/A                          |
| WEIGHT (G)                      | 200.0                        |



|                           |   |
|---------------------------|---|
| PRODUCT GROUPS            | Cable   |
| ON-BOARD TX BUFFER        | No  |
| CERTIFICATIONS            | CE,RoHS   |
| CURRENT CONSUMPTION       | N/A   |
| CB BOARD                  | No  |
| CLOCK SYNC                | No  |
| PRODUCT GROUPS            | Cable   |
| ERROR FRAME DETECTION     | N/A   |
| EMBEDDED SCRIPT           | No  |
| MSGRATE RX MAX            | N/A   |
| API, FREE                 |   |
| PROMOTIONAL_TEXT          | Adapter cable for the Kvaser PCICanx 4xHS and Kvaser PCICan 4xHS. |
| PROMOTIONAL_TEXT          | Kvaser PCICanx 4xHS Kvaser PCICan 4xHS                            |
| ON-BOARD TX BUFFER        | N/A   |
| TIMESTAMP RESOLUTION (US) | N/A   |
| LENGTH (MM)               | 300   |
| RUGGED                    | No  |
| HEIGHT (MM)               | N/A   |
| SOUND                     | N/A   |
| EMBEDDED SCRIPT           | No  |
| MSGRATE TX MAX            | N/A   |
| CERTIFICATIONS            | CE,RoHS   |
| GALVANIC ISOLATION        | No  |
| ON-BOARD BUFFER           | No  |
| NETWORK CHANNEL(S)        |   |
| CURRENT CONSUMPTION       |   |
| CASING MATERIAL           |   |



|                           |  |  |
|---------------------------|--|--|
| IP CLASS                  |  | N/A  |
| ERROR FRAME DETECTION     |  | No   |
| WIDTH (MM)                |  | N/A  |
| WIDTH (MM)                |  | N/A  |
| HEIGHT (MM)               |  | N/A  |
| MSGRATE RX MAX            |  | N/A  |
| TIMESTAMP RESOLUTION (US) |  | N/A  |
| CLOCK SYNC                |  | N/A  |
| # OF CAN CHANNELS         |  | 4  |
| CB BOARD                  |  | No   |
| API, LICENCED             |  |  |
| RUGGED                    |  | No   |
| IP CLASS                  |  |  |
| MINIMUM BITRATE (KBPS)    |  | N/A  |
| SILENT MODE               |  | No   |
| CONNECTOR                 |  | N/A  |
| STATUS                    |  | Active   |
| DATABASE DBC SUPPORT      |  | No   |
| OPERATING SYSTEM          |  | Win XP, Linux, Win 7, Win Vista, Win 10, Win 8 |
| ON-BOARD BUFFER           |  | N/A  |
| MSGRATE TX MAX            |  | N/A  |
| OPERATING SYSTEM          |  | Win XP, Linux, Win 7, Win Vista, Win 10, Win 8 |
| CAN FD                    |  | No   |

The information herein is subject to change without notice