

ATI

SmartTach

ATI's SmartTach Module is a universal speed measurement tool for measurement applications such as engine RPM, vehicle speed, chassis dyno roll speed, frequency, period, pulse width and duty cycle.

The built-in User Interface allows the SmartTach to be easily configured without a PC connection. This provides access to the advanced features and functions of the SmartTach.




Features

- Analog Voltage Output proportional to measurement
- Conditioned Digital Pulse Output
- RS-232 Serial Interface
- Programmable Range Outputs
- In-vehicle, stand-alone or rackmount

Specifications

Signal Inputs	
Pulse Inputs	Selectable between Spark (Coil Primary, Inductive Pickup) and Trigger (Digital, VRS) modes Measurement range from 0.5Hz to 500KHz Trigger voltage range +/- 75 V Intelligent signal conditioning in Trigger Mode
Analog Voltage Input	Auxiliary analog voltage input used together with range outputs Input voltage levels may be programmed along with range outputs 0 to 5 V input range
Signal Outputs	
Analog Voltage Output	Optically isolated analog voltage output proportional to measurement Programmable scaling, offset and range in engineering units Maximum output range 0 to 10 V 12-bit D/A (+/- 0.003 V resolution)
Digital Pulse Output	Optically isolated digital 5V conditioned pulse output corresponding to input signal May be used to connect to other instrumentation requiring conditioned signals
Range Outputs	Three user programmable range outputs Speed ranges for output activation may be independently programmed Optically isolated solid state relay (contact-closure) outputs
Other Inputs/Outputs	
Communication Port	RS-232 Serial Port, 75 - 9600 baud The Serial Port may be used for obtaining data from the unit and for remote configuration
Power Supply	Requires 10-30 VDC at 10W maximum Internal regulated power supply
General	
Enclosure	Aluminum and steel, black color, water and oil resistant Dimensions: (WDH) 141 x 138 x 39 mm/ 5.57 x 5.45 x 1.52 in Weight: 0.58 kg / 1.3 lbs



SmartTach Details

Easy Installation

All that is needed for RPM / speed measurement is a repetitive pulse signal and DC power. The SmartTach is compatible with a wide variety of input signal sources such as: Inductive pickups, magnetic sensors, encoders, ECU outputs and direct connection to an ignition coil. The SmartTach uses microprocessor controlled intelligent signal conditioning. This allows the SmartTach to dynamically configure the signal conditioning when using the magnetic sensors or digital pulses.

Timing Patterns

Compatible with "patterned" (i.e. missing or extra tooth) crankshaft position signals. Popular automotive patterns are pre-programmed and additional custom patterns can be easily programmed by the operator. Maximum achievable transient timing measurement accuracy is always obtained for any given reference pattern.

SmartTach Order Information

Product

Part Number	Description
100-0005	SmartTach

Accessories

Part Number	Description
Accessory	
100-0007	10m/32.8ft TachSensor with 15-pin D-sub connector; measures engine speed when clamped around an Ignition Primary wire
100-0009	3.66m/12ft
100-0011	10m/32.8ft Optical Diesel RPM Pickup w/sensor; measures speed of any rotating object
100-0014	3.66m/12ft Inductive Spark Plug Wire Sensor: measures spark event (or engine speed) when clamped around a Secondary Ignition cable
Power	
102-0006	DC Power Plug, 2-pin open connector
102-0002	Dual DC-Power Plug with Wire, Y-cable Adapter
100-0006	AC/DC Power Supply with AC Cord
Package	
100-0016	SmartTach with 19 in Rackmount System, includes (1) SmartTach, (1) power supply, (1) bracket, and (1) blank rack cover
Hardware	
102-0001	19 in 1HU rack mount designed for mounting one or two units in a cabinet
102-0003	Blank Rack Cover Plate (covers holes on bracket)

Accurate Technologies Inc. is continually improving its products and reserves the right to alter the specifications of its products at any time without notice.

Contact ATI Sales at:

sales@accuratetechnologies.com

France +33 (0) 1 72 76 26 10
Germany +49 (0) 89 9700 7121
India +91 80 41694218
Japan +81 3 5325 6222
Sweden +46 (0) 31 773 7140
UK +44 (0) 1767 652 340
US +00 (1) 248 848 9200